



STAR
SMART
BUILDING SOLUTIONS

THE ULTIMATE TILE CLEANER



PRODUCT DESCRIPTION

Star TiloKlean is a high-quality, rapid-action cleaner and degreasing solution designed for use on tiles, bathtubs, washbasins, privy basins, and concrete surfaces. It effectively removes whitish spots or layers that commonly appear in bathrooms under plastic or metal buckets—where normal detergents are often ineffective. It also ensures quick removal of white or yellowish stains, water marks, cement stains, grime, oil, paint stains, grease, moss, and wax from surfaces such as concrete, asbestos, terrazzo, and ceramics.

APPLICATION AREAS



Suitable for cleaning floor & wall tiles

- Kitchens • Bathrooms • Toilets
- Garages • Factories • General building sites • Residential areas



Can be used for both internal and external tiling, in domestic as well as commercial spaces.



Ideal for routine tile cleaning using a mop in bathrooms and other tiled areas.

ADVANTAGES



Easy to Use

Just mix with water and clean the surface effortlessly.



Removes Tough Stains

Fast and effective against stubborn dirt and marks.



Powerful Degreasing

Easily removes soap scum, efflorescence, and mineral deposits.



Versatile Cleaning

Safe for ceramic, porcelain, and vitrified tiles – including grout.



Colour & Shine Protection

Maintains the natural color & gloss of your tiles.



Joint-Friendly Formula

Does not damage tile joints, even with colored grouting.



Acid-Free & Safe

Gentle on surfaces – not harmful like acids.

APPLICATION PROCEDURE

For Mild Stains or Layers

A Mix Star TiloKlean with water in a 1:1 ratio.



B Soak a cloth or sponge in a diluted solution and rub the surface until the stains/layers are removed.



For Stubborn Stains or Heavy Layers

A Use undiluted Star TiloKlean (without mixing with water).



B Test on a small area first before applying over the entire surface.



For Routine Tile Cleaning

A Dilute two capfuls of Star TiloKlean in half a bucket of water.



B Use the diluted solution to clean tiles and sanitaryware regularly.



LIMITATIONS

- Test Before Use
- Always test Star TiloKlean on a small corner area before applying on Coloured concrete, Granite, Marble flooring and Other natural stones.
- Observe for 24 hours
- If any discolouration or surface etching appears within 24 hours, do not use the product on that surface.

TECHNICAL INFORMATION

PHYSICAL & APPLICATION PROPERTIES

Testing Properties	Test Results
Density	1.02 +/- 0.02 kg/litre
Colour	Reddish liquid
Viscosity	Equal to water
Soaking Time	5 minutes
Dilution with Water	Dilution with water will depend upon substrate condition and stain severity

COVERAGE

Coverage depends on the porosity and level of contamination of the surface (substrate).

SHELF LIFE

The shelf life of Star TiloKlean is 12 months for sealed packs when stored under cover, away from direct sunlight, in a dry and damp-proof area, and protected from extreme temperatures.

SAFETY PRECAUTIONS



Keep out of reach of children.



Wear suitable protective clothing, gloves, and eye/face protection.



In case of contact with skin, wash immediately with plenty of clean water. If it meets eyes, rinse thoroughly with water and seek medical advice. Intended for professional use only.

STAR SBS

PRODUCTS



STAR
SMART
BUILDING SOLUTIONS

Product Portfolio

- ✓ **STAR AAC**
Alternative to Clay Bricks
- ✓ **STAR Block Jointing Mortar**
Adhesive for Joining the AAC Blocks
- ✓ **STAR TiloSetter** Tile Adhesive
TiloSetter - For Small Floor Tiles
Premium - For Medium Floor & Wall Tiles
Elite - For Stone & Large Floor & Wall Tiles
Ultima - For Heavy Marbles & Glass Mosaic Tiles
- ✓ **STAR TiloKlean** Tiles Cleaning Solution
- ✓ **STAR GroutSolidSeal (Cement Based)**
To Fill Up Gaps for Domestic Tiles
- ✓ **STAR GroutSolidSeal (Epoxy Based)**
To Fill Up Gaps for Industrial & Commercial Tiles
- ✓ **STAR RMX Ready Mix Plaster**
For both Interior & Exterior Plastering of Walls
- ✓ **STAR WaterPruf**
Integral Waterproofing Compound
W1 - Concrete Mix
- ✓ **STAR WaterPruf** SBR Latex
W2 - Concrete Protector
W3 - For Hairline Cracks
W4 - For Hairline Cracks (Premium)
W5 - For Cracks up to 1mm
W6 - For Cracks up to 2mm
- ✓ **STAR UltimaSmooth Wall Putty**
For Creating a Smooth & Even Wall Surface
- ✓ **STAR Dhalai Master CoverBlock**
For Ensuring Reinforcing Bars or Rebars are put into the Concrete at the Proper Depth

Star Smart Building Solutions Ltd.

Gopinath Bordoloi Road, Vill. Chamatapathar, Dist. Kamrup(M), Guwahati – 782402, Assam

www.starcement.co.in | Toll Free No.: 1800 345 345 00 |  **Star Cement**